

Why choose Intel Xeon 6 processors as host CPUs?

Intel Xeon processors are the host CPUs of choice for the world's most powerful AI accelerator platforms, being the most benchmarked host processors for these systems.¹

Here are five more reasons to choose Intel Xeon 6 processors as your host CPUs for AI-accelerated systems.

1

Superior I/O performance

Higher input/output (I/O) bandwidth accelerates data offloads and elevates operational efficiency.

Boost I/O bandwidth with up to **20 percent more PCIe lanes** than the previous generation (up to 192 PCIe 5.0 lanes per processor).

2

Higher core counts and single-threaded performance

Higher CPU core counts and single-threaded performance translate into faster data feeds for GPUs/accelerators, which helps shorten models' time-to-train. High max turbo processor frequencies boost single-threaded CPU performance.

Up to **128 P-cores per CPU** deliver 2x more cores per socket than the previous generation.

3

Higher memory bandwidth and capacity

Intel Xeon 6 is the first processor family to introduce Multiplexed Rank DIMMs (MRDIMMs). This innovative memory technology boosts bandwidth, performance, and latency for memory-bound AI and HPC workloads. Intel Xeon 6 processors support (2) DIMMs per memory channel, enabling large memory capacities which are important for AI systems that need to support ever increasing AI model sizes and data sets.

Intel Xeon 6 processors feature up to 504 MB L3 cache, combined with support from Compute Express Link (CXL). CXL maintains memory coherency between the CPU memory space and memory on attached devices.

MRDIMMs deliver **up to 2.3x higher memory bandwidth** compared to the previous generation.²

CXL enables **high-performance resource sharing, reduced software stack complexity, and lower overall system cost.**

4

Dedicated RAS support

Intel's industry-leading reliability, availability, and serviceability (RAS) support reduces costly downtime for large AI/HPC systems. Advanced management capabilities include telemetry, platform monitoring, control over shared resources, and real-time firmware updates. RAS benefits from the collective expertise of platform partners, ISVs, and solution integrators.

Minimize business disruptions with Intel Xeon 6 processors, **built to maximize uptime** and operational efficiency.

5

Flexibility for mixed workloads

Intel Xeon 6 processors are designed to support a wide variety of workloads as host CPUs, delivering both performance and efficiency. In some cases, host CPUs in AI systems might need to support limited AI functionality during the data preprocessing phase.

Intel® Advanced Matrix Extensions (Intel® AMX) includes **newly added support for FP16** precision arithmetic to support data preprocessing and other host CPU responsibilities in AI-accelerated systems.

Learn about additional benefits that Intel Xeon 6 processors can deliver as the host CPU of choice for AI-accelerated systems:

intel.com/content/www/us/en/products/details/processors/xeon.html.

See how Intel Xeon 6 processors enhance AI/HPC workloads.

Examine the latest workload performance metrics:

<https://edc.intel.com/content/www/us/en/products/performance/benchmarks/intel-xeon-6/>.

Review product specifications and find the best processor

for your unique computing needs:

<https://ark.intel.com/content/www/us/en/ark/products/series/595/intel-xeon-processors.html>.

¹ Based on MLPerf benchmark testing as of 2024. For details, visit <https://mlcommons.org/>.

² Based on Intel analysis as of May 2024. **Baseline:** 1-node, 2 x Intel Xeon Platinum 8592+ processors, 64 cores, Intel® Hyper-Threading Technology (Intel® HT Technology) on, Intel® Turbo Boost Technology on, NUMA configuration SNC2, 1,024 GB total memory (16 x 64 GB DDR5 5,600 megatransfers per second [MT/s]), BIOS version 3B07.TEL2P1, microcode 0x21000200, Ubuntu 24.04, Linux version 6.8.0-31-generic, tested by Intel as of May 2024. **New:** 1-node, pre-production platform, 2 x Intel Xeon 6 processors with P-cores, Intel HT Technology on, Intel Turbo Boost Technology on, NUMA configuration SNC3, 3,072 GB total memory (24 x 128 GB MCR 8,800 MT/s), BIOS version BHSDCRB1.IPC.0031.D97.2404192148, microcode 0x81000200, Ubuntu 23.10, kernel version 6.5.0-28-generic. **Software:** NEMO v4.2.2. ORCA025 dataset from CMCC. Intel® Fortran Compiler Classic and Intel® MPI from 2024.1; Intel® oneAPI HPC Toolkit. Compiler flags "-i4 -r8 -O3 -xCORE-AVX2 -fno-alias -fp-model fast=2 -align array64byte -fimf-use-svml=true."